

POSIFLEX

Powerful yet Thrifty



PS-3615-G2

Best Value Fanless POS Terminal

Crafted with functionality and flexibility in mind, PS-3615-G2 Series features a 15" wide touch screen, fanless technology, and an adjustable base to scale to meet both retailers' and consumers' expectations—all within an affordable, yet attractive and feature-rich terminal.

PS-3615-G2

Specification		PS-3615-G2
Processor		Intel Elkhart Lake Celeron J6412, up to 2.60 GHz, 1.5M Cache
System Memory		DDR4 SO-DIMM x 1, max. 16GB
Storage Device		M.2 connector (SATA Signal Only) x 1
TPM		Yes, TPM 2.0
Power Supply		12V/60W
OS Support		Windows 10 IoT 64 bit

Display & Touch

LCD		15" TFT LCD
Resolution		1024 x 768
Touch		True-flat PCAP touch with multi-touch support (IP65 on front panel)

I/O & Expansion

Serial Port		4, DB9 x 3 + RJ45 x 1, 5V/12V support on all COM ports
Parallel Port		1, via optional conversion cable through service window
Standard USB Port		5, USB 3.0 x 2+ USB 2.0 x 2 (on I/O plate) + USB 2.0 x 1 (on the top)
PoweredUSB Port		Optional 24V x 1 + 12V x 3 via GEN8 base
OTG USB		N/A
LAN Port		10/100/1000 Mb x 1
Display Port		VGA x 1, 12V support for Posiflex monitors
CR Port		1, control 2 CR via optional Y-cable, supporting 24V cash drawer
PS/2 Port		1, via optional conversion cable through service window
Audio		Buzzer x 1; Optional internal 2W speaker x 1
Expansion Slot		M.2 slot x 1

Physical Dimension

Dimension (W x D x H in mm)		372 x 252.7 x 320
Weight (N. W. in kg)		5.86

Environmental

Operating Condition		0°C - 50°C, 20%RH - 90%RH (Equipped with SSD)
Storage Condition		-20°C - 70°C, 10%RH - 90%RH

Built-in Options

WiFi		M.2 WiFi/BT module
------	--	--------------------

Attachment Options

POS Monitor		Non-touch TFT USB LCD: 7"/9.7"
Line Display		2 x 20 rear-mount VFD customer line display; 2 x 20 rear-mount LCD customer line display; 7" color LCD graphical line display
Attachment		MSR; iButton; RFID; Fingerprint Sensor; Keypad

*Designed and Manufactured in Taiwan by Posiflex Technology, Inc.

*The product information and specifications are subject to change without prior notice.

*Please refer to the website for more attachment options.

Certifications	      	EN2020720V3
----------------	--	-------------

POSIFLEX

POSIFLEX TECHNOLOGY, INC.

No. 23, Datong St., Tucheng Dist., New Taipei City 23679, Taiwan

Tel : +886-2-2268-5577 E-mail : sales@posiflex.com.tw

Fax : +886-2-2268-5388 www.posiflex.com

Authorized Distributor / Reseller