



P/N:

ST-CE1075-2-UEVL ST-CE1075-2-UEVL-MB1 (bundled with SignoSign/2)

SUPPORTED OS

Windows® XP 32/64, W7 32/64, W8 32/64, W10 32/64 Server 2003, 2008, 2010 Linux

CERTIFICATIONS AND STATEMENT OF COMPLIANCE

TUV CE, FCC RoHS EN 60950-1, EN 61000-6-1, EN 61000-6-3

PROTECTION CLASS

IP52

COLOR SIGNATURE PAD

The Sig200 is a powerful signature pad for ultra-ergonomic signing.

Its large and color sensitive display is ideal to optimize the signature process on a counter or desktop.

With its programmable memory, a content can be displayed to show graphics or promotional messages, contributing to improve your company's brand image.

TECHNICAL DATA

GENERAL FEATURES	Slim and ergonomic designStandard stylusTether2 LED status indicators
DISPLAY	 5" (12.5 cm) Full-color TFT Real-time signature display Backlit display 65 000 colors 640 x 480 pixels
SENSOR	 Resistive touch technology Active signing area: 101 x 76 mm Resolution: 4096 x 4096 pixels / 1388 x 1040 ppi Linearity: +/- 1.5% in x, y and z directions 1024 pressure levels
DIGITIZATION	 External sampling rate: 500 Hz (samples per second), 4 axes (x, y, time and pressure) Internal sampling rate: 6000 Hz (samples per second)
SECURITY	 AES encryption of data transfer between the pad and the computer RSA signature and encryption in the pad Unique internal serial number
SIZE AND WEIGHT	• 15 x 180 x 191 mm (0.59" x 7.08" x 7.52") • 356 g (0.79 lbs)
INTERFACE	Full-speed (12 Mbps) USB 2.0 HID (Human Interface Device) compatible with earlier versions
POWER	Via USB cable, no external power supply
SOFTWARE	 Compatible with signoSign/2 software for creating and signing secure PDF documents Free SDK available upon request: Definition of signature area Signature capture in various formats RSA-signing functionality in the pad Documentation available on demand Free tools and Twain driver available at www.evolis.com
WARRANTY	• 2 years